

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional BITUM SPRAY

Date of issue: 20.06.2016

Version: 1.0/EN

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Spray Professional BITUM SPRAY

1.2 Details of the supplier of the safety data sheet

Relevant identified uses: asphalt based product intended for anticorrosion covering of chassis and boats.

Uses advised against: not determined.

1.3 Details of the supplier of the safety data sheet

Supplier: CHAMPION COLOR PLUS P. Lelito Sp. J.

Address: ul. Dworcowa 7 84-123 Potchowo, Poland

Telephone number /Fax: +48 58 673-94-36/+48 58 673-94-22

E-mail address for a competent person responsible for sds: biuro@theta-doradztwo.pl

1.4 Emergency telephone number

112

+48 58 673-94-36 (between 8.00-15.00)

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Aerosol 1 H222-H229, Asp. Tox. 1 H304*, Skin Irrit. 2 H315, STOT SE 3 H336, Repr. 2 H361fd, Aquatic Chronic 3 H412

Extremely flammable aerosol. Pressurised container: May burst if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. Suspected of damaging the unborn child. Harmful to aquatic life with long lasting effects.

*product does not require labelling in terms of this hazard if it is placed on the market on the market in aerosol containers.

2.2 Label elements

Hazard pictograms and signal words



DANGER

Product identifier

Contains: naphtha (petroleum), hydrotreated light, hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional BITUM SPRAY

Date of issue: 20.06.2016

Version: 1.0/EN

H336 Causes serious eye irritation
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P263 Avoid contact during pregnancy.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

2.3 Other hazards

Product does not contain ingredients, which meet criteria for PBT or vPvB in accordance with Annex XIII of REACH Regulation.

Section 3: Composition/information on ingredients

3.1 Substances

Not applicable.

3.2 Mixtures

hydrocarbons, C3-4, petroleum gas*

Concentration range: 30-40%
CAS number: 68476-40-4
EC number: 270-681-9
Index number: 649-199-00-1
Registration number: 01-2119486557-22-XXXX
Classification: Flam. Gas 1 H220, Liq. Gas H280

* classification as a carcinogen or mutagen need not apply, because substance contains less than 0,1 % 1,3-butadiene (Note K).

hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Concentration range: < 30%
CAS number: -
ECHA list number: 919-857-5
Index number: -
Registration number: 01-2119463258-33-XXXX
Classification: Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336

naphtha (petroleum), hydrotreated light*

Concentration range: < 15%
CAS number: 64742-49-0
EC number: 265-151-9
Index number: 649-328-00-1

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional BITUM SPRAY

Date of issue: 20.06.2016

Version: 1.0/EN

Registration number: 01-2119475133-43-XXXX
Classification: Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Eye Irrit. 2 H319, STOT SE 3 H336, Repr. 2 H361fd, Aquatic Chronic 2 H411

* classification after taking into account note P, substance contains < 0,1% w/w benzene CAS: 71-43-2. Product contains toluene and n-hexane, substances with Community level exposure limits in the workplace.

Full text of each relevant R and H phrase is given in section 16 of SDS.

Section 4: First aid measures

4.1 Description of first aid measures

Skin contact: take off contaminated clothes immediately. Wash contaminated skin with water, then wash out with plenty of water with soap. Consult a doctor, if disturbing symptoms occur.

Eye contact: seek medical advice if irritation occurs. Rinse the contaminated eyes with plenty of water for 15-20 minutes. Remove any contact lenses, protect non-irritated eye. Avoid strong stream of water – risk of damage of the cornea.

Ingestion: exposure by this route does not typically occur. If swallowed, rinse mouth with water. Do not induce vomiting! Never give anything by mouth to an unconscious person. Consult a doctor – show label.

Inhalation: remove to fresh air. Keep warm and calm. Perform artificial respiration or give oxygen if needed. Consult a doctor, if disturbing symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

Skin contact: may cause skin dryness or cracking after repeated exposure, defatting, frostbite after spraying the product on skin spray at close range, temporary irritation.

Eye contact: irritation, burning sensation, redness, tearing.

Ingestion: may cause irritation of the mucous membranes of gastrointestinal tract, nausea, vomiting. Vomiting with risk of chemical pneumonia.

Inhalation: possible irritation of the mucous membranes of respiratory system, drowsiness and dizziness.

Other exposure effects: suspected of damaging fertility and the unborn child.

4.3 Indication of any immediate medical attention and special treatment needed

Physician makes a decision regarding further medical treatment after thoroughly examination of the injured. Treat symptomatically.

Section 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: carbon dioxide (CO₂), alcohol resistant foam, dry chemical, water fog. Small fire put out with the snow extinguisher (CO₂) or dry powder (ABC or BC), large fire extinguish with alcohol-resistant foam or water fog. Large fire should be extinguished from protected posts.

Unsuitable extinguishing media: water jet – risk of propagation of the flame.

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional BITUM SPRAY

Date of issue: 20.06.2016

Version: 1.0/EN

5.2 Special hazards arising from the substance or mixture

Under fire conditions product may produce harmful gases consisting of carbon oxides and other unidentified thermal decomposition products. Do not inhale combustion products, they may cause health risk. Pressurized container – risk of unsealing or even explosion in high temperature.

5.3 Advice for firefighters

Personal protection typical in case of fire. Do not stay in the fire zone without self-contained breathing apparatus and protective clothing resistant to chemicals. Do not allow extinguishing water to enter drains, surface water and groundwater. Gas can accumulate on the surface of the ground and move along distances creating a risk of fire or explosion. Cool containers at risk of fire from a safe distance with water spray. Collect used extinguishing media.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Limit the access for the outsiders into the breakdown area, until the suitable cleaning operations are completed. Ensure that the effects of breakdown are removed only by trained personnel. In case of large spills, isolate the exposed area. Avoid eyes and skin contamination. Do not inhale aerosol. Ensure adequate ventilation. Wear adequate personal protective equipment. Remove all sources of ignition, do not use open flames or sparking tools. Prohibit smoking.

6.2 Environmental precautions

In case of release of large amounts of the product, it is necessary to take appropriate steps to prevent it from spreading into the environment. Notify relevant emergency services.

6.3 Methods and material for containment and cleaning up

Collect damaged container mechanically. Absorb leakage with incombustible liquid-binding material (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to appropriate waste disposal containers. Clean contaminated surface. Do not use sparking tools, do not smoke. Treat the collected material as waste.

6.4 Reference to other sections

Appropriate conduct with waste product – section 13. Personal protection equipment – section 8.

Section 7: Handling and storage

7.1 Precautions for safe handling

Handle in accordance with good occupational hygiene and safety practices. Avoid contact with skin and eyes. Do not inhale aerosol. Ensure adequate general and/or local ventilation. Eliminate sources of ignition - do not use open flames, do not smoke, do not use sparking tools and clothing from fabric susceptible to electrification; protect containers from heating. Do not spray on a naked flame or any incandescent material. Protect against electrostatic charges. Pregnant women should not work with this product. Use personal protective equipment.

7.2 Conditions for safe storage, including any incompatibilities

Store only in a cool, dry place, recommended storage temperature: up to + 35°C. Keep away from sources of ignition and heat. Do not smoke, use open flame and sparking devices in a warehouse. Do not pierce or burn packaging even after use.

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional BITUM SPRAY

Date of issue: 20.06.2016

Version: 1.0/EN

Keep away from food, foodstuffs and animal feed. Avoid contact with strong oxidizing agents (concentrated nitric acid, hydrogen peroxide, organic peroxides) - contact may cause ignition. Avoid contact with steel corrosive agents (acids, salt solutions) - the risk of damaging of the containers and releasing of aerosols content.

7.3 Specific end use(s)

No information about uses other than mentioned in subsection 1.2.

Section 8: Exposure controls/personal protection

8.1 Control parameters

Specification	Limit values	
	8 hours	short term
toluene [CAS 108-88-3]	192 mg/m ³	384 mg/m ³
n-hexane [CAS 110-54-3]	72 mg/m ³	—

Legal Basis: Commission Directive 2006/15/EC, 2000/39/EC, 2009/161/EC.

The table above shows the maximum workplace concentration values at the Community level.

Please check any national occupational exposure limit values in your country.

Recommended control procedures

Procedures Concerning the control over the dangerous components concentrations in the air and control over the air quality in the workplace - if they are available and Justified for the position - in Accordance with the European Standards, with the conditions within the exposure place and a proper test methodology adapted to the working conditions.

8.2 Exposure controls

Use the product in accordance with good occupational hygiene and safety practices. Do not eat, drink or smoke when using the product. Take off contaminated clothes immediately. Ensure good general and/or local ventilation at work stations to ensure the maintenance of concentrations of hazardous components in the air below the exposure limit values. Before break and after work wash hands carefully. Avoid eyes and skin contamination. If there is a risk of inflammation of the clothing on worker, emergency showers for washing entire body and separate eyewash stations should be installed no more than 20 m in a straight line from the working area where these processes are performed.

Hand protection

Use gloves resistant to the product (e.g. made from butyl rubber). In case of short term contact use protective gloves with effectiveness level 2 or higher (permeation time > 30 minutes). In case of long term contact use protective gloves with effectiveness level 6 (permeation time > 480 minutes). Using protective cream on exposed parts of the body is recommended.

When using protective gloves during work with chemical products, it should be noted that the efficacy levels and corresponding breakthrough times do not indicate actual times of protection at a particular workplace, because the protection can be affected by many factors, e.g. temperature, other substances etc. If there are any signs of degradation, damage or change in appearance (colour, flexibility, shape), it is recommended to replace the gloves with a new pair. Please follow the manufacturer's instructions, not only in terms of gloves' usage, but also in terms of their cleaning, maintenance and storage. It is also important to know how to take off the gloves in order to avoid hands contamination.

Body protection

Antistatic protective clothing made of dense fabric (preferably from natural fibers, such as cotton).

Safety boots.

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional BITUM SPRAY

Date of issue: 20.06.2016

Version: 1.0/EN

Eye protection

Safety glasses in a sealed enclosure with side protection (plastic casing resistant to organic solvents).

Respiratory protection

Under normal conditions of use is not required. In case of insufficient ventilation, wear an approved respirator with a filter of AX type. Use breathing apparatus with independent air supply in case of: working in a confined space, insufficient amount of oxygen in the air, a large uncontrolled emissions or other circumstances when the mask with the filter does not give a sufficient protection.

Personal protective equipment must meet requirements of directive 89/686/CE. Employer is obliged to ensure equipment adequate to activities carried out, with quality demands, cleaning and maintenance.

Environmental exposure controls

Avoid environment contamination, do not empty into drains. Possible emissions from the ventilation systems and processing equipment should be controlled in order to determinate their compatibility with environmental protection regulations.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

physical state/form:	liquid in aerosol container
colour:	according to specification
odour:	characteristic
odour threshold:	not determined
pH:	not applicable
melting point/freezing point:	not determined
initial boiling point and boiling range:	not determined
flash point:	not determined
evaporation rate:	not determined
flammability (solid, gas):	extremely flammable aerosol
upper/lower flammability or explosive limits:	not determined
vapour pressure:	not determined
vapour density:	not determined
density:	not determined
solubility(ies):	not determined
partition coefficient: n-octanol/water:	not determined
auto-ignition temperature:	not determined
decomposition temperature:	not determined
explosive properties:	not display
oxidising properties:	not display
viscosity dynamic:	not determined

9.2 Other information No additional data.

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional BITUM SPRAY

Date of issue: 20.06.2016

Version: 1.0/EN

Section 10: Stability and reactivity

10.1 Reactivity

Product is reactive. Product vapours may create explosive mixtures with air. See subsections 10.3 – 10.5.

10.2 Chemical stability

The product is stable under normal conditions of handling and storage.

10.3 Possibility of hazardous reactions

Product vapours may form explosive mixtures with air.

10.4 Conditions to avoid

Avoid sources of heat and direct sunlight, temperature above 50°C.

10.5 Incompatible materials

Avoid contact with strong oxidizers.

10.6 Hazardous decomposition products

Not known.

Section 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging fertility. Suspected of damaging the unborn child.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Product contains components with low viscosity which are classified as hazardous after aspiration caused by ingestion. However, due to the form of the product, preventing accidental ingestion, the whole product does not pose aspirational hazard.

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional BITUM SPRAY

Date of issue: 20.06.2016

Version: 1.0/EN

Section 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data for mixture.

12.3 Bioaccumulative potential

No data for mixture.

12.4 Mobility in soil

Product is mobile in aquatic environment and soil. Gaseous components quickly spread in atmosphere. Mobility of components of the mixture in soil depends on the hydrophilic and hydrophobic properties and biotic and abiotic conditions of soil, including its structure, climatic conditions, seasons and soil organisms (mostly: bacteria, fungus, algae, invertebrates).

12.5 Results of PBT and vPvB assessment

Substances contained in the product are not assessed as PBT and vPvB.

12.6 Other adverse effects

The mixture is not classified as hazardous to the ozone layer. Consider other harmful effects of individual components of the mixture on the environment (eg, endocrine disrupting potential, global warming potential).

Section 13: Disposal considerations

13.1 Waste treatment methods

Disposal methods for the product: do not empty into drains. Disposal in accordance with the local legislation. Do not remove the product from the original packaging. Recommended waste code: 16 03 05* Organic wastes containing dangerous substances. Waste code should be given in the place of its formation.

Disposal methods for used packing: classification of the waste meets the requirements for hazardous waste. Deliver the packaging to an authorized company. Do not mix with other waste materials. Do not burn and do not pierce the empty package.

Legal basis: Directive 2008/98/EC, 94/62/EC.

Section 14: Transport information

14.1 UN number

UN1950

14.2 UN proper shipping name

AEROSOLS, flammable

14.3 Transport hazard class(es)

2 (label 2.1)



Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional BITUM SPRAY

Date of issue: 20.06.2016

Version: 1.0/EN

14.4 Packing group

Not applicable. Limited quantities 1I.

14.5 Environmental hazards

Mixture is hazardous for the environment according to the criteria of transport regulations.

14.6 Special precautions for user

Avoid sources of ignition and fire. Packages should not be thrown or subjected to impact. Receptacles shall be so placed on the vehicle or container that they cannot tip over or fall.

EMS: F-D, S-U (IMDG code for shipping).

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC as amended.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Text with EEA relevance) as amended.

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste and repealing certain Directives.

European Parliament and Council Directive 94/62/EC of 20 December 1994 on packaging and packaging waste

15.2 Chemical safety assessment

It is not necessary to carry out a chemical safety assessment for the mixture.

Section 16: Other information

Full text of indicated H phrases mentioned in section 3

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional BITUM SPRAY

Date of issue: 20.06.2016

Version: 1.0/EN

H336	May cause drowsiness or dizziness.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations and acronyms

PBT	Persistent, Bioaccumulative and Toxic substance
vPvB	very Persistent, very Bioaccumulative substance
DNEL	Derived No Effect Level.
PNEC	Predicted No Effect Concentration
Flam. Gas 1	Flammable gas category 1
Press. Gas	Gas under pressure
Skin Irrit. 2	Skin irritation category 2
Flam. Liq. 2,3	Flammable liquid category 2,3
STOT SE 3	Specific target organ toxicity — single exposure category 3
Aquatic Chronic 2	Hazardous to the aquatic environment category 2
Asp Tox. 1	Aspiration hazard
Repr. 2	Reproductive toxicity category 2

Trainings

Before commencing working with the product, the user should learn the Health & Safety regulations, regarding handling chemicals, and in particular, undergo a proper workplace training. Persons related to the transportation of the dangerous goods in compliance with the ADR Agreement should be properly trained within the scope of performed tasks (general training, on-the-job training and training related to the safety issues).

Other data

Classification of the mixture was made on the basis of calculation method based on the guidelines of Directive 1999/45/EC and Regulation 1272/2008/EC (CLP) as amended

Data of issue: 20.06.2016

Version: 1.0/EN

Composed by: mgr Paweł Jędrzejczyk (on the basis of producer's data)

Safety Data Sheet made by: „THETA” Doradztwo Techniczne

The information above is based on a current available data concerning the product, but also on the experience and knowledge in this field of the producer. They are neither a quality description of the product nor a guarantee of particular features. They are to be treated as aid to safety in transport, storage and usage of the product. That does not free the user from the responsibility of improper usage of the information above and also of improper compliance with the law norms in the field.