

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional PODKŁAD NA ZDERZAKI

Date of issue: 27.06.2016

Version: 1.0/EN

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Spray Professional PODKŁAD NA ZDERZAKI

1.2 Details of the supplier of the safety data sheet

Relevant identified uses: a primer for topcoat decorative paints for variety of surfaces made of polypropylene and other plastics, intended for spray application.

Uses advised against: not determined.

1.3 Details of the supplier of the safety data sheet

Supplier: CHAMPION COLOR PLUS P. Lelito Sp. J.

Address: ul. Dworcowa 7 84-123 Potchowo, Poland

Telephone number /Fax: +48 58 673-94-36/+48 58 673-94-22

E-mail address for a competent person responsible for sds: biuro@theta-doradztwo.pl

1.4 Emergency telephone number

112

+48 58 673-94-36 (between 8.00-15.00)

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Aerosol 1 H222-H229, Asp. Tox. 1 H304*, Skin Irrit. 2 H315, Eye Irrit. 2 H319, STOT SE 3 H336, Repr. 2 H361d, STOT RE 2 H373

Extremely flammable aerosol. Pressurised container: May burst if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs (central nervous system) through prolonged or repeated exposure.

*product does not require labelling in terms of this hazard if it is placed on the market on the market in aerosol containers.

2.2 Label elements

Hazard pictograms and signal words



DANGER

Names of substances required for labelling

Contains: toluene; ethyl methyl ketone.

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional PODKŁAD NA ZDERZAKI

Date of issue: 27.06.2016

Version: 1.0/EN

H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P263 Avoid contact during pregnancy.
P271 Use only outdoors or in a well-ventilated area.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.
P501 Dispose of contents/container to hazardous or special waste collection point.

2.3 Other hazards

Product does not contain ingredients, which meet criteria for PBT or vPvB in accordance with Annex XIII of REACH Regulation.

Section 3: Composition/information on ingredients

3.1 Substances

Not applicable.

3.2 Mixtures

toluene

Concentration range: 35-40%
CAS number: 108-88-3
EC number: 203-625-9
Index number: 601-021-00-3
Registration number: -
Classification: Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Repr. 2 H361d, STOT RE 2 H373

Substance with European Union level exposure limit in the workplace.

hydrocarbons, C3-4, petroleum gas*

Concentration range: 28-40%
CAS number: 68476-40-4
EC number: 270-681-9
Index number: 649-199-00-1
Registration number: 01-2119486557-22-XXXX
Classification: Flam. Gas 1 H220, Liq. Gas H280

The classification as a carcinogen or mutagen need not apply, because substance contains less than 0,1 % 1,3-butadiene (Note K).

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional PODKŁAD NA ZDERZAKI

Date of issue: 27.06.2016

Version: 1.0/EN

ethyl methyl ketone

Concentration range: 20-30%
CAS number: 78-93-3
EC number: 201-159-0
Index number: 606-002-00-3
Registration number: 01-2119457290-43-XXXX
Classification: Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336
EUH066 – additional phrase code indicating hazard type
Substance with Community level exposure limit in the workplace.

xylene

Concentration range: 3-5%
CAS number: 1330-20-7
EC number: 215-535-7
Index number: 601-022-00-9
Registration number: 01-2119488216-32-XXXX
Classification: Flam. Liq. 3 H226, Asp. Tox. 1 H304, Acute Tox. 4 H312, Skin Irrit. 2 H315, Eye Irrit. 2 H319, Acute Tox. 4 H332, STOT SE 3 H335, STOT RE 2 H373
Substance with Community level exposure limit in the workplace.
Full text of each relevant H phrase is given in section 16 of SDS.

Section 4: First aid measures

4.1 Description of first aid measures

Skin contact: take off contaminated clothes immediately. Wash contaminated skin with water, then wash out with plenty of water with soap. Consult a doctor, if disturbing symptoms occur.

Eye contact: seek medical advice if irritation occurs. Rinse the contaminated eyes with plenty of water for 15-20 minutes. Remove any contact lenses, protect non-irritated eye. Avoid strong stream of water – risk of damage of the cornea.

Ingestion: exposure by this route does not typically occur. If swallowed, rinse mouth with water. Do not induce vomiting! Never give anything by mouth to an unconscious person. Consult a doctor – show label.

Inhalation: remove to fresh air. Keep warm and calm. Perform artificial respiration or give oxygen if needed. Consult a doctor, if disturbing symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

Skin contact: may cause skin dryness or cracking after repeated exposure, defatting, frostbite after spraying the product on skin spray at close range, irritation.

Eye contact: irritation, burning sensation, redness, tearing.

Ingestion: due to the form of the product exposure by this way is impossible.

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional PODKŁAD NA ZDERZAKI

Date of issue: 27.06.2016

Version: 1.0/EN

Inhalation: high concentration of aerosol may lead to irritation of mucous membrane of respiratory tract, dizziness and drowsiness, headaches, tiredness.

Other adverse effects: may cause damage to central nervous system through prolonged or repeated exposure. Suspected of damaging the unborn child.

4.3 Indication of any immediate medical attention and special treatment needed

Physician makes a decision regarding further medical treatment after thoroughly examination of the injured. Treat symptomatically.

Section 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: carbon dioxide (CO₂), alcohol resistant foam, dry chemical, water fog. Small fire put out with the snow extinguisher (CO₂) or dry powder (ABC or BC), large fire extinguish with alcohol-resistant foam or water fog. Large fire should be extinguished from protected posts.

Unsuitable extinguishing media: water jet – risk of propagation of the flame.

5.2 Special hazards arising from the substance or mixture

Under fire conditions product may produce harmful gases consisting of carbon oxides and other unidentified thermal decomposition products. Do not inhale combustion products, they may cause health risk. Pressurized container – risk of unsealing or even explosion in high temperature.

5.3 Advice for firefighters

Personal protection typical in case of fire. Do not stay in the fire zone without self-contained breathing apparatus and protective clothing resistant to chemicals. Do not allow extinguishing water to enter drains, surface water and groundwater. Gas can accumulate on the surface of the ground and move along distances creating a risk of fire or explosion. Cool containers at risk of fire from a safe distance with water spray. Collect used extinguishing media.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Limit the access for the outsiders into the breakdown area, until the suitable cleaning operations are completed. Ensure that the effects of breakdown are removed only by trained personnel. In case of large spills, isolate the exposed area. Avoid eyes and skin contamination. Do not inhale aerosol. Ensure adequate ventilation. Wear adequate personal protective equipment. Remove all sources of ignition, do not use open flames or sparking tools. Prohibit smoking.

6.2 Environmental precautions

In case of release of large amounts of the product, it is necessary to take appropriate steps to prevent it from spreading into the environment. Notify relevant emergency services.

6.3 Methods and material for containment and cleaning up

Collect damaged container mechanically. Absorb leakage with incombustible liquid-binding material (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to appropriate waste disposal containers. Clean contaminated surface. Do not use sparking tools, do not smoke. Treat the collected material as waste.

6.4 Reference to other sections

Appropriate conduct with waste product – section 13. Personal protection equipment – section 8.

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional PODKŁAD NA ZDERZAKI

Date of issue: 27.06.2016

Version: 1.0/EN

Section 7: Handling and storage

7.1 Precautions for safe handling

Handle in accordance with good occupational hygiene and safety practices. Avoid contact with skin and eyes. Do not inhale aerosol. Ensure adequate general and/or local ventilation. Eliminate sources of ignition - do not use open flames, do not smoke, do not use sparking tools and clothing from fabric susceptible to electrification; protect containers from heating. Do not spray on a naked flame or any incandescent material. Protect against electrostatic charges. Use personal protective equipment.

7.2 Conditions for safe storage, including any incompatibilities

Store only in a cool, dry place, recommended storage temperature: up to + 35°C. Keep away from sources of ignition and heat. Do not smoke, use open flame and sparking devices in a warehouse. Do not pierce or burn packaging even after use. Keep away from food, foodstuffs and animal feed. Avoid contact with strong oxidizing agents (concentrated nitric acid, hydrogen peroxide, organic peroxides) - contact may cause ignition. Avoid contact with steel corrosive agents (acids, salt solutions) - the risk of damaging of the containers and releasing of aerosols content.

7.3 Specific end use(s)

No information about uses other than mentioned in subsection 1.2.

Section 8: Exposure controls/personal protection

8.1 Control parameters

Specification	Limit values	
	8 hours	short term
toluene [CAS 108-88-3]	192 mg/m ³	384 mg/m ³
ethyl methyl ketone [CAS 78-93-3]	600 mg/m ³	900 mg/m ³
xylene [CAS 1330-20-7]	221 mg/m ³	442 mg/m ³

Legal Basis: Commission Directive 2006/15/EC, 2000/39/EC, 2009/161/EC.

The table above shows the maximum workplace concentration values at the Community level.

Please check any national occupational exposure limit values in your country.

Recommended control procedures

Procedures Concerning the control over the dangerous components concentrations in the air and control over the air quality in the workplace - if they are available and Justified for the position - in Accordance with the European Standards, with the conditions within the exposure place and a proper test methodology adapted to the working conditions.

DNEL values for components

DNEL	xylene	
	worker	consumer
inhalation, short-term exposure (local / systemic effects)	289 mg/m ³	174 mg/m ³
inhalation, long-term exposure (local / systemic effects)	77 mg/m ³	14,8 mg/m ³

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional PODKŁAD NA ZDERZAKI

Date of issue: 27.06.2016

Version: 1.0/EN

skin, long-term exposure (systemic effects)	180 mg/kg b. w./day	108 mg/kg b. w./day
oral, long-term exposure (systemic effects)	—	1,6 mg/kg b. w./day

8.2 Exposure controls

Use the product in accordance with good occupational hygiene and safety practices. Do not eat, drink or smoke when using the product. Take off contaminated clothes immediately. Ensure good general and/or local ventilation at work stations to ensure the maintenance of concentrations of hazardous components in the air below the exposure limit values. Before break and after work wash hands carefully. Avoid eyes and skin contamination. If there is a risk of inflammation of the clothing on worker, emergency showers for washing entire body and separate eyewash stations should be installed no more than 20 m in a straight line from the working area where these processes are performed.

Hand protection

Use gloves resistant to the product (e.g. made from butyl rubber). In case of short term contact use protective gloves with effectiveness level 2 or higher (permeation time > 30 minutes). In case of long term contact use protective gloves with effectiveness level 6 (permeation time > 480 minutes). Using protective cream on exposed parts of the body is recommended.

When using protective gloves during work with chemical products, it should be noted that the efficacy levels and corresponding breakthrough times do not indicate actual times of protection at a particular workplace, because the protection can be affected by many factors, e.g. temperature, other substances etc. If there are any signs of degradation, damage or change in appearance (colour, flexibility, shape), it is recommended to replace the gloves with a new pair. Please follow the manufacturer's instructions, not only in terms of gloves' usage, but also in terms of their cleaning, maintenance and storage. It is also important to know how to take off the gloves in order to avoid hands contamination.

Body protection

Antistatic protective clothing made of dense fabric (preferably from natural fibers, such as cotton).
Safety boots.

Eye protection

Safety glasses in a sealed enclosure with side protection (plastic casing resistant to organic solvents).

Respiratory protection

Under normal conditions of use is not required. In case of insufficient ventilation, wear an approved respirator with a filter of AX type. Use breathing apparatus with independent air supply in case of: working in a confined space, insufficient amount of oxygen in the air, a large uncontrolled emissions or other circumstances when the mask with the filter does not give a sufficient protection.

Personal protective equipment must meet requirements of directive 89/686/CE. Employer is obliged to ensure equipment adequate to activities carried out, with quality demands, cleaning and maintenance.

Environmental exposure controls

Avoid environment contamination, do not empty into drains. Possible emissions from the ventilation systems and processing equipment should be controlled in order to determinate their compatibility with environmental protection regulations.

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional PODKŁAD NA ZDERZAKI

Date of issue: 27.06.2016

Version: 1.0/EN

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

physical state/form:	aerosol
colour:	colorless
odour:	characteristic, solvent-like
odour threshold:	not determined
pH:	not applicable
melting point/freezing point:	not determined
initial boiling point and boiling range(1013 hPa):	-42 do 142°C (propane, xylene respectively)
flash point:	- 105°C (propane)
evaporation rate:	not determined
flammability (solid, gas):	extremely flammable
upper/lower flammability or explosive limits:	9,6/1,9 % vol. (for propellant)
vapour pressure:	> 0,1MPa (-15°C), < 2,55 MPa (70°C) – for propellant
vapour density (air=1):	> 1
density (20°C):	ca. 0,7 kg/dm ³
solubility(ies):	0,012 kg/dm ³ (water)
partition coefficient: n-octanol/water:	not determined
auto-ignition temperature:	> 287°C
decomposition temperature:	not determined
explosive properties:	not display, but product vapours can create explosive mixtures with air
oxidising properties:	not display
viscosity dynamic:	not determined

9.2 Other information

No additional data.

Section 10: Stability and reactivity

10.1 Reactivity

Product is reactive. See subsections 10.3 – 10.5.

10.2 Chemical stability

The product is stable under normal conditions of handling and storage.

10.3 Possibility of hazardous reactions

Product vapours may form explosive mixtures with air.

10.4 Conditions to avoid

Avoid sources of heat and direct sunlight, temperature above 50°C.

10.5 Incompatible materials

Avoid contact with strong oxidizers.

10.6 Hazardous decomposition products

Not known.

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional PODKŁAD NA ZDERZAKI

Date of issue: 27.06.2016

Version: 1.0/EN

Section 11: Toxicological information

11.1 Information on toxicological effects

Toxicity of ingredients

xylene [CAS 1330-20-7]

LC₅₀ (skin, rabbit) 1 700 mg/kg

Toxicity of mixture

Acute toxicity

ATEmix (skin) > 2000 mg/kg

ATEmix (inhalation, vapours) > 20 mg/l

ATEmix (inhalation, mists) > 5 mg/l

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs (central nervous system) through prolonged or repeated exposure.

Aspiration hazard

Product contains components with low viscosity which are classified as hazardous after aspiration caused by ingestion. However, due to the form of the product, preventing accidental ingestion, the whole product does not pose aspirational hazard.

Section 12: Ecological information

12.1 Toxicity

Toxicity of ingredients

hydrocarbons C₃₋₄ [CAS 68476-40-4]

Acute toxicity for fish LC₅₀ > 24,11 mg/l/96h (*Oncorhynchus mykiss*)

Acute toxicity for daphnia EC₅₀ > 14,22 mg/l/48h (*Daphnia magna*)

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional PODKŁAD NA ZDERZAKI

Date of issue: 27.06.2016

Version: 1.0/EN

ethyl methyl ketone [CAS 78-93-3]

Acute toxicity for fish	LC ₅₀	> 100 mg/l/96h (<i>Leuciscus idus</i>)
Acute toxicity for daphnia	EC ₅₀	> 100 mg/l/48h (<i>Daphnia magna</i>)
Acute toxicity for algae	EC ₅₀	> 100 mg/l/7d (<i>Desmodesmus subspicatus</i>)

Toxicity of mixture

Product is not classified as hazardous for aquatic environment.

12.2 Persistence and degradability

No data for mixture.

xylene [CAS 1330-20-7]

undergoes biodegradation in 70% within 10 days.

toluene [CAS 108-88-3]

undergoes biodegradation in 86% within 20 days.

12.3 Bioaccumulative potential

No data for mixture.

xylene [CAS 1330-20-7]

log Po/w = 3,15.

BCF = 25,9.

toluene [CAS 108-88-3]

log Po/w = 2,73.

BCF = 90.

12.4 Mobility in soil

Product is mobile in aquatic environment and soil. Gaseous components quickly spread in atmosphere. Mobility of components of the mixture in soil depends on the hydrophilic and hydrophobic properties and biotic and abiotic conditions of soil, including its structure, climatic conditions, seasons and soil organisms (mostly: bacteria, fungus, algae, invertebrates).

12.5 Results of PBT and vPvB assessment

Substances contained in the product are not classified as PBT and vPvB.

12.6 Other adverse effects

The mixture is not classified as hazardous to the ozone layer. Consider other harmful effects of individual components of the mixture on the environment (eg, endocrine disrupting potential, global warming potential).

Section 13: Disposal considerations

13.1 Waste treatment methods

Disposal methods for the product: do not empty into drains. Disposal in accordance with the local legislation. Do not remove the product from the original packaging. Recommended waste code: 16 03 05* Organic wastes containing dangerous substances. Waste code should be given in the place of its formation.

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional PODKŁAD NA ZDERZAKI

Date of issue: 27.06.2016

Version: 1.0/EN

Disposal methods for used packing: classification of the waste meets the requirements for hazardous waste. Deliver the packaging to an authorized company. Do not mix with other waste materials. Do not burn and do not pierce the empty package.

Legal basis: Directive 2008/98/EC, 94/62/EC.

Section 14: Transport information

14.1 UN number

UN 1950

14.2 UN proper shipping name

AEROSOLS, flammable



14.3 Transport hazard class(es)

2 (label 2.1)

14.4 Packing group

Not applicable. Limited quantities 1I.

14.5 Environmental hazards

Mixture is hazardous for the environment according to the criteria of transport regulations.

14.6 Special precautions for user

Avoid sources of ignition and fire. Packages should not be thrown or subjected to impact. Receptacles shall be so placed on the vehicle or container that they cannot tip over or fall.

EMS: F-D, S-U (IMDG code for shipping).

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC as amended.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Text with EEA relevance) as amended.

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste and repealing certain Directives.

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional PODKŁAD NA ZDERZAKI

Date of issue: 27.06.2016

Version: 1.0/EN

European Parliament and Council Directive 94/62/EC of 20 December 1994 on packaging and packaging waste

15.2 Chemical safety assessment

It is not necessary to carry out a chemical safety assessment for the mixture.

Section 16: Other information

Full text of indicated H phrases mentioned in section 3

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H280	Pressurized gas, may burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH 066	Repeated exposure may cause skin dryness or cracking.

Abbreviations and acronyms

PBT	Persistent, Bioaccumulative and Toxic substance
vPvB	very Persistent, very Bioaccumulative substance
DNEL	Derived No Effect Level.
PNEC	Predicted No Effect Concentration
Eye Irrit. 2	Eye irritation category 2
Skin Irrit. 2	Skin irritation category 2
Flam. Liq. 2	Flammable liquid category 2
STOT SE 3	Specific target organ toxicity — single exposure category 3
STOT RE 2	Specific target organ toxicity – repeated exposure category 2
Acute Tox. 4	Acute toxicity category 4
Press. Gas	Pressurized gas
Flam. Gas 1	Flammable gas category 1
Aquatic Chronic 2	Hazardous to the aquatic environment category 2
Asp Tox. 1	Aspiration hazard category 1
Repr. 2	Reproduction toxicity category 2

Trainings

Before commencing working with the product, the user should learn the Health & Safety regulations, regarding handling chemicals, and in particular, undergo a proper workplace training. Persons related to the transportation of the dangerous goods in compliance with the ADR Agreement should be properly trained within the scope of performed tasks (general training, on-the-job training and training related to the safety issues).

Safety Data Sheet

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Spray Professional PODKŁAD NA ZDERZAKI

Date of issue: 27.06.2016

Version: 1.0/EN

Other data

Classification of the mixture was made on the basis of calculation method based on the guidelines of Directive 1999/45/EC and Regulation 1272/2008/EC (CLP).

Data of update: 27.06.2016

Version: 1.0/EN

Composed by: mgr Paweł Jędrzejczyk (on the basis of producer's data)

Safety Data Sheet made by: „THETA” Doradztwo Techniczne

The information above is based on a current available data concerning the product, but also on the experience and knowledge in this field of the producer. They are neither a quality description of the product nor a guarantee of particular features. They are to be treated as aid to safety in transport, storage and usage of the product. That does not free the user from the responsibility of improper usage of the information above and also of improper compliance with the law norms in the field.